



Devco Australia Holdings Pty Ltd

P O Box 14, Pinkenba Qld 4008

Ph +61 7 3260 2361

ABN 45 098 077 662

Fx +61 7 3260 2431

www.sulphur.com.au

SUPERFINE PRILLED SULPHUR

Product Specification

Product Code: SFPS

| TEST | UNIT | LIMIT |
|--|----------|---------------------|
| Colour | | Bright Yellow |
| Shape | | Generally spherical |
| Size | | ~ 50 µm – 1 mm |
| Purity of Sulphur | % mass | 99.8 % minimum |
| Carbon | % mass | 0.1 % maximum |
| Ash | % mass | 0.1 % maximum |
| Acidity (H ₂ SO ₄) | % mass | 0.02 % maximum |
| H ₂ S | % mass | 20 ppm maximum |
| Moisture | % mass | 5 % maximum |
| Arsenic | ppm mass | 20 ppm maximum |
| Cadmium | ppm mass | 5 ppm maximum |
| Copper | ppm mass | 20 ppm maximum |
| Chloride | ppm mass | 20 ppm maximum |
| Fluoride | ppm mass | 20 ppm maximum |
| Lead | ppm mass | 1.0 ppm maximum |
| Mercury | ppm mass | 1.0 ppm maximum |
| Selenium | ppm mass | 0.1 ppm maximum |

Notes

1. Testing frequency and reporting requirements to be agreed with customer.
2. Refer to the Material Safety Data Sheet for safe handling information.

| | | | |
|--------------|--|-------------|---------------|
| Author: | Allen Bromley | Issued: | 22 July 2009 |
| Approved by: | Allen Bromley | Supersedes: | 21 April 2009 |
| Doc. Name: | Product Specification Super Fine Prilled Sulphur | | |