



Devco Australia Holdings Pty Ltd

P O Box 14, Pinkenba Qld 4008 ♦ Ph +61 7 3260 2361

ABN 45 098 077 662

www.sulphur.com.au

SUPERFINE PRILLED SULPHUR

Product Specification

Product Code: SF

TEST	UNIT	TYPICAL ANALYSIS
Colour		Bright Yellow
Shape		Generally spherical
Size		~ 50 micron – 1 mm
Purity of Sulphur	% mass	99.8 % minimum
Carbon	% mass	0.1 % maximum
Ash	% mass	0.1 % minimum
Acidity (H ₂ SO ₄)	% mass	0.02 % maximum
H ₂ S	% mass	20 ppm maximum
Moisture	% mass	5 % maximum
Arsenic	ppm mass	2 ppm maximum
Cadmium	ppm mass	2 ppm maximum
Copper	ppm mass	20 ppm maximum
Chloride	ppm mass	20 ppm maximum
Fluorine	ppm mass	150 ppm maximum
Lead	ppm mass	10 ppm maximum
Mercury	ppm mass	0.1 ppm maximum
Selenium	ppm mass	0.1 ppm maximum

Notes

1. Testing frequency and reporting requirements to be agreed with customer.
2. Refer to the Material Safety Data Sheet for the safe handling information.

Author:	Guil Araldi	Issued:	28 Aug 2024
Approved by:	Richard Aston	Supersedes:	5 August 2021
Doc. Name:	Product Specification Superfine Prilled Sulphur		